

Eight Strand Plaited Anchor Rod (With G4 HT Chain)



Eight Strand Plaited Anchor Rod (With G4 HT Chain) is pre-spliced and ready to use. Special marking tape is included for marking the rode at increments. Check manufacturer's specification prior to purchase.

PART ID	ROPE		CHAIN		TOTAL LENGTH	SAFE WORKING LOAD lb / kg / kn	BREAKING STRENGTH lb / kg / kn
	DIA	LENGTH	WIRE DIA	LENGTH			
10517980	1/2" / 12 mm	150' / 45 m	1/4" / 6 mm	15' / 5 m	165' / 50 m	1134 / 504 / 5	5670 / 2522 / 25
10517982	1/2" / 2 mm	200' / 60 m	1/4" / 6 mm	15' / 5 m	215' / 65 m	1134 / 504 / 5	5670 / 2522 / 25
10517984	1/2" / 12 mm	250' / 75 m	1/4" / 6 mm	15' / 5 m	265' / 80 m	1134 / 504 / 5	5670 / 2522 / 25
10517986	1/2" / 12 mm	300' / 90 m	1/4" / 6 mm	20' / 6 m	320' / 96 m	1134 / 504 / 5	5670 / 2522 / 25
10525077	1/2" / 12 mm	150' / 45 m	1/4" / 6 mm	25' / 7.5 m	175' / 53 m	1134 / 504 / 5	5670 / 2522 / 25
10525078	1/2" / 12 mm	150' / 45 m	1/4" / 6 mm	50' / 15 m	200' / 60 m	1134 / 504 / 5	5670 / 2522 / 25
10525079	1/2" / 12 mm	200' / 60 m	1/4" / 6 mm	50' / 15 m	250' / 75 m	1134 / 504 / 5	5670 / 2522 / 25
10525080	1/2" / 12 mm	250' / 75 m	1/4" / 6 mm	50' / 15 m	300' / 90 m	1134 / 504 / 5	5670 / 2522 / 25
10525081	5/8" / 16 mm	150' / 45 m	5/16" / 8 mm	25' / 7.5 m	175' / 53 m	2330 / 1040 / 10	11650 / 5200 / 52
10525082	5/8" / 16 mm	150' / 45 m	5/16" / 8 mm	50' / 15 m	200' / 60 m	2330 / 1040 / 10	11650 / 5200 / 52
10525083	5/8" / 16 mm	200' / 60 m	5/16" / 8 mm	50' / 15 m	250' / 75 m	2330 / 1040 / 10	11650 / 5200 / 52
10525084	5/8" / 16 mm	250' / 75 m	5/16" / 8 mm	50' / 15 m	300' / 90 m	2330 / 1040 / 10	11650 / 5200 / 52

Warning: Working Load Limit must not be exceeded. Not to be used for lifting or hoisting applications.