

Anchor Chain




GALVANISED SHORT LINK CHAIN

Manufactured from mild steel, this calibrated chain is welded for high strength and hot dipped galvanized for minimal corrosion. Available in a selection of sizes and formations, it will fit all Muir chain gypsies as well as other windlass brands.

Grade L Short Link Chain

The most widely used certified anchor chain. Grade L is the highest quality lower tensile steel chain for lifting purposes.

Chain Size mm	WWL (tonne)	D (mm)	P (mm)	W (mm)	Links/m	Metres/100kg
6	0.4	6.3	18.8	21.6	53	110
8	0.64	8	23.8	27.8	42	69.9
10	1	10	29.8	34	33.6	43.9
13	1.7	12.5	38	42	26.5	28.9



ABBREVIATIONS

D Dia **W** width
P Pitch **MWL** Max wkg load/tonne

WWL Max mass which the chain hanging vertical shall support in general service

Note: Link dimensions and metres/100kg subject to commercial tolerances. Larger sizes and types available eg studlink, refer to Mega Catalogue or contact nearest Muir office.

ANCHOR AND SWIVEL SHACKLES

Grade S hot dipped galvanized and stainless steel shackles for all marine and commercial applications, ideally suited to Muir anchor chain. Available in bow and dee type with screw collar pins. Available for all chain and anchor types and sizes. Swivel shackles are available in galvanized and stainless steel to suit all chain sizes.

Note: Chain supply may vary in countries outside Asia/Pacific Region.

